

Plastering Made Easy

Betonit EzyPLAST is a high quality acrylic solution intended as concrete admixture designed for interior and exterior use. It is suitable as a Plastering Aid as well as a Bonding Aid.

Applications

PLASTERING AID

Mix with plaster mortar to improve adhesion, tensile, flexural and compressive strengths, and improve elasticity of fresh plaster coat.

BONDING AID

Mix with portland cement to form a bonding slurry coat between old concrete and fresh plaster or skim coat. Also suitable for patching and repair works.

Advantages

PLASTERING AID

- Reduces cracking and shrinkage of plaster coat
- Controls water loss in mortar for proper curing
- Increases bonding of plaster coat to masonry wall
- Increases the abrasion resistance of concrete
- Reduces brittleness of concrete.

BONDING AID

- Improves bonding of new to old concrete
- Eliminates the need for concrete surface roughening or scarifying work.



Betonit™

Ezyplast

ACRYLIC LATEX ADMIXTURE
& BONDING AGENT

How to use:

SURFACE PREPARATION:

- All concrete surfaces must be properly cured before plastering or screeding work commences. Uneven or cracked areas must be properly repaired and exposed bars appropriately cleaned and primed.
- Clean concrete surfaces thoroughly by removing all loosely adhering particles, dirt, oils, paints and other contaminants.
- DAMPEN THE SUBSTRATE BEFORE APPLYING THE PLASTER OR THE BONDING SLURRY.

PLASTERING AID

Mix Betonit EzyPlast with water in a clean container. Use guidelines on mixing ratios.

REGULAR STRENGTH



HEAVY DUTY



OR



+



Add solution to cement and sand to desired consistency.

PLASTERING ON MORTAR APPLICATION MUST BE CARRIED OUT WHILE THE BONDING SLURRY IS TACKY.

BONDING AID

Mix equal parts of Betonit EzyPlast and Portland cement until a creamy slurry is attained. Using a notched trowel or stiff brush, apply a 1-2 mm thin coat of slurry prior to applying thick bed plaster of mortar.



APPLY THICK BED PLASTER OR MORTAR WHILE SLURRY IS STILL TACKY, USUALLY WITHIN 20 MINUTES.

Coverage: one (1) gallon will cover approx. 20 sqm

PRODUCT PACKAGE SIZE: 4 Liter Bottles
POTLIFE: 1 hour

USE PROTECTIVE WEAR



SHAKE WELL BEFORE USING



MINIMUM SETTING TIME



STORE IN COOL DRY PLACE



SHELF LIFE



It all starts with good plastering.